

Leads, Cords, Cables & Clips



Item Number
ABL-36 INCH

ABL-36 INCH

Black Silicone Test Lead

100 cm long with shielded, stackable, retractable banana plugs

The ABL-36 INCH is a Black High Resistance Silicone Test Lead with 2 each shielded, stackable retractable plugs for use with the PAR-809B Variable Resistance Reference and the PGB-745 Decay Accessory Set.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
ARL-36 INCH

ARL-36 INCH

Red Silicone Test Lead

100 cm long with shielded, stackable, retractable banana plugs

The ARL-36 INCH is a Red High Resistance Silicone Test Lead with 2 each shielded, stackable retractable plugs for use with the PAR-809B Variable Resistance Reference and the PGB-745 Decay Accessory Set.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PFP-861 LL

PFP-861 LL 72 inch Test Lead

72 inch test lead for use with PFP-861 Stainless Steel Test Plate

The PFP-861 LL is a 72 inch Green Pomona Lead used for grounding and footwear test purposes.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)

**Continued on
Next Page**



Item Number
PRF-911 GGL

PRF-911 GGL

Green Silicone Test Lead

Green grounding lead for PRF-911 Concentric Ring Fixture

The PRF-911 GGL is a Green High Resistance Silicone Test Lead with 2 each stackable retractable plugs used to ground the PRF-911 Concentric Ring or for general grounding purposes.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRS-800 L

PRS-800 L 10 foot

Silicone Test Lead

10 foot silicone lead for use with PRS-800, PRS-801, PRS-812

10 foot high resistance silicone insulated test lead. Right angle banana plug on one end and a shielded male banana plug on the other.

Test lead to be used with the PRS-800 Megohmmeter, PRS-801 Resistance System Set or PRS-812 Resistance Meter Set.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRS-800 SSL

PRS-801 SSL Shielded Test Lead

High Resistance Shielded test lead for use with PRS-801

This High Resistance Shielded test lead is used to make high end resistance measurements with the PRS-801 Resistance System Set or PRS-812 Resistance Meter Set.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)

Continued on
Next Page



Item Number
PRS-801 TVL

**PRS-801 TVL High
Resistance Voltage Test Lead**
High Resistance Voltage Test Lead for use with PRS-801

This High Resistance Voltage test lead is used in conjunction with the PRS-801 SSL High Resistance Shielded test lead to make high end resistance measurements with the PRS-801 Resistance System Set or PRS-812 Resistance Meter Set.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PFM-711 AC

PFM-711 AC Analog Output Cable
Analog output cable for use with PFM-711A Field Meter

The analog output cable is used to connect to the PFM-711A Field Meter for use with an X-Y Plotter, analog data recorder or timing device.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRS-801

PRS-801 CIC Computer Input Cable
36 inch computer input cable for PRS-801

The PRS-801 CIC, for use with the PRS-801 Resistance System Set, is a RS-232 Data Transmission Cable to standard I/O COM 9 Pin computer ports that let you download your data to standard computer systems via the instrument's RS-232 Output Port.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRs-800CS

PRs-800CS Cable Spacers 36 & 10 inch length Cable Spacers with Insulated ends

This set consists of one 10 inch and one 36 inch Cable Spacer. These are convenient for measuring Point-to-Point according to ESD STM7.1 and ESD STM4.1 using the PRs-801-W 5 lb Conductive Rubber Electrodes.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRs-801BC

PRs-801BC Bulldog Clip Insulated black bulldog clip for use with PRs-800, PRs-801 and PRs-812

4mm safety plug-on alligator clip, rated 1000V, CAT II, 32A, is fully insulated in polyamide 6.6 and features marked handling areas and overlapping side panels.

This rugged crocodile clip is heavily sprung for good clamping and its brass hinge assures good current distribution.

The clip has a 4 mm rigid socket to accept standard and safety leads and a jaw opening of approximately 20 mm. The clip weighs 13 g.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRI-870 IAC

PSI-870 IAC Insulated Alligator Clip Alligator clip for PSI-870 Rtg use

Handy accessory clips useful for grounding to equipment and parts.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)



Item Number
PRI-870 MAC

PSI-870 MAC Alligator Clip Bare metal alligator clip

Handy accessory clips useful for grounding to equipment and parts.

Packaging

Weight: 1 lbs (0.5 kg)
Length: 8.25 Inches (21 cm)
Width: 7.5 Inches (19 cm)
Height: 3.5 Inches (8.5 cm)