

# ZeroStat Access

## Anti-Static Maintainer for Access Flooring

**Improves appearance and ease of maintenance**

**Helps maintain the static dissipative properties of access flooring**

**Not a coating or floor finish, won't flow between or through access tiles**

**Never builds-up or requires "stripping"**

**Single application covers up to 800 square feet**

### PRODUCT DESCRIPTION

Representing a new concept in high performance floor care, this remarkable burnishing cream cleans and enhances the appearance of antistatic access flooring, while improving the ease of maintenance and static dissipative properties. ZeroStat Access utilizes a special combination of detergents, surfactants, and resins that penetrate the pores in access flooring, forming a subsurface, antistatic barrier that resists dirt and soil. ZeroStat Access's special ingredients do not form a film or build up, and never require "stripping" like antistatic floor finishes.

### APPLICATION & MAINTENANCE

Clean floor surfaces with a dust mop or vacuum to remove loose dirt and soil. If floors are soiled, damp mop using ZeroStat Access. Apply a three-to-four inch line of ZeroStat Access to the floor and distribute it evenly over a white or beige high speed polishing pad by briefly activating the buffing or burnishing machine. Fine dirt and soil will be suspended and discharged out the sides of the burnishing pad and should be swept up following the application.

### SAFETY INFORMATION

Health	1
Flammability	1
Reactivity	0
Personal Protection	B

**CAUTION:** May cause eye and skin irritation. If eye contact occurs, flush with plenty of water and get immediate medical attention. For skin contact, wipe off area with a towel and rinse with plenty of water. If swallowed, induce vomiting and get immediate medical attention. Read Material Safety Data Sheet thoroughly before using.

### SPECIFICATIONS

Nonvolatile Solids	3 - 4%
Total Active	18%
pH	7.8-8.5
Color	White Emulsion
Weight Per Gallon	8.1
Stability	1 year minimum at room temperature
Freeze/Thaw Stability	3 cycles maximum
Water Resistance	Excellent
Coverage per 4" Applic.	500 - 800 feet <sup>2</sup>

Product No.

**6049**



4916 26th Street West  
Suite 100  
Bradenton, Florida 34207  
Toll Free: 877-463-1376  
Direct Phone: 941-751-7581