



Ground Zero Electrostatics TRANSITIONS AND REDUCERS

TRANSITIONS AND REDUCERS

Ground Zero's static control vinyl mouldings are available in 25 colors and 55 different shapes for every transitional and joining application. This means you can meet all of your transitional requirements while maintaining your color coordination.

The line includes some specialty mouldings such as the corner guards and tub mouldings.

Joining Mouldings

These mouldings help to join two different types and/or thicknesses of flooring to each other.

Cove Supports

Mouldings support sheet vinyl when covered up the wall.

Transitional Mouldings

Achieve transition from carpet, resilient tiles, resilient sheet vinyl, ceramic, and wood to 0 inches.

Edge Finishing Mouldings

These mouldings help to finish the exposed edges of covered sheet vinyl, covered carpet, ceramic tile and wood paneling. Shapes 225, 230 and 400 can also be used

as walk-off transitions.

Mat Edging Mouldings

Flexible vinyl for protecting edges of floor mats.

Threshold Mouldings

Designed to cover joint in doorways.

Corner Guards

Flexible corner guards in 3 sizes.

Tub Mouldings

Cove for bathtub, counter and shelves

COLOR SELECTION



PRODUCT DETAILS

Applications Legend:




Meets ADA Requirements

Mouldings that meet the requirements of sections 4.5.2 (change in level) and 4.5.3 (carpet-edge trim compliance) of the Americans with Disabilities Act (ADA) are indicated with **blue profiles**.

Part #	App.	Profile	Description	Packaging
TS-150 Tile-"COLOR" Carpet Joiner	 		One-piece moulding. Joins 1/4" (6.350 mm) carpet to 1/8" (3.175 mm) tile.	25-12' secs. Per carton (300 feet)
TS-152-"COLOR" Carpet to Resilient Transition	 		Transitions 1/4" (6.350 mm) or 5/16" (7.938 mm) glue-down carpet to 1/16" (1.588 mm) to 1/8" (3.175 mm) resilient.	20-12' secs. Per carton (240 feet)
TS-153-"COLOR" Cerco Bar 3/8"	 		One-piece moulding for joining 5/16" (7.938 mm) carpet to 3/8" (9.525 mm) ceramic materials.	10-12' secs. Per carton (120 feet)
TS-360-"COLOR" Cerco T	 		Snap-in T moulding. Joins 1/2" (12.700 mm) material. Uses 970, 980, or 990 track only.	20-12' secs. Per carton (240 feet)
TS-365-"COLOR" Cerco Edge T	 		Joins 1/2" (12.700 mm) material to lesser-gauge material. Uses 970, 980, or 990 track only.	20-12' secs. Per carton (240 feet)


**TS-710-"COLOR"
Carpet to Resilient
Transition**



Transitions 1/4" (6.350 mm) or 5/16" (7.938 mm) glue-down carpet to 1/8" (3.175 mm) resilient.

10-12' secs. Per carton (120 feet)


**TS-930-"COLOR"
Snap-Down T**



Snap-in T moulding. Joins 1/4" (6.350 mm) or 5/16" (7.938 mm) material on each side. Uses 970, 980, or 990 track only.

20-12' secs. Per carton (240 feet)


**TS-935-"COLOR"
Super 2" T**



Snap-in T moulding. Joins 1/4" (6.350 mm) or 5/16" (7.938 mm) material on each side. Uses 970, 980, and 990 track only.

20-12' secs. Per carton (240 feet)

**TS-940 Standard
Edge T**



Joins 1/4" (6.350 mm) to lesser-gauge. 1 1/4" (31.750 mm) wide; 1/4" (6.350 mm) leg. Uses 970, 980, or 990 track only.

20-12' secs. Per carton (240 feet)


**TS-970 Single
Flange Vinyl Track
(400 Natural only)**



For 1/4" (6.350 mm) and 1/2" (12.700 mm) leg T portions. Use with 360, 365, 930, 935 & 940 T's.

20-12' secs. Per carton (240 feet)


**TS-980 Pinless
Metal Track**



Designed to install T mouldings 360, 365, 930, 935 and 940. Aluminum.

48-12' secs. Per carton (576 feet)

**TS-990 Metal
Track with pins**



Designed to install T mouldings 360, 365, 930, 935 and 940. Aluminum.

48-12' secs. Per carton (576 feet)



Ground Zero Electrostatics TRANSITIONS AND REDUCERS

INSTALLATION

Generally these parts are glued, nailed, tacked or stapled into place. There are many products in this line and they all have various ways that they can be installed. Each installation may have different installation requirements, depending on that particular job situation.

If you have any general or specific installation questions please contact your Ground Zero representative.

RECCOMENDED ADHESIVES

The recommended adhesive for Ground Zero Mouldings is a flammable, solvent-based contact cement. Liquid Nails can also be used.

MAINTENANCE

Mild soap and water should readily clean most situations. A polish is not necessary, however, a liquid floor polish can be used if glossy shine or extra protection are desired or if it is convenient due to being adjacent to a polished surface.

For any maintenance problems, call your Ground Zero representative for assistance.

AVAILABILTIY AND COSTS

Ground Zero Mouldings can be obtained from local distributors throughout the United States and Canada. For the name of your local distributor handling Ground Zero Mouldings, contact your Ground Zero representative.

WARRANTIES

Ground Zero Mouldings: 2 Year Limited Warranty

All Products Will:

- ☀ Be free from defects in material and workmanship at the time of shipment
- ☀ Conform, within reasonable variation allowable for this industry, to the description (size, color, pattern) on the sales order
- ☀ Be sufficiently packaged and labeled
- ☀ Not wear out within their respective warranty periods if properly installed, maintained, and used in the right conditions

Warranties Will Be Void If:

- ☀ Ground Zero Adhesives are not used
- ☀ Products are not installed and maintained according to
- ☀ Ground Zero instructions
- ☀ Products are not first quality (i.e. seconds, imperfects)



4916 26th Street West, Suite 100, Bradenton, Florida 34207

Toll Free 877-GND-ZERO (463-1376), **Direct Phone** 941-751-7581 **Fax** 1-941-751-7586

Email sales@gndzero.com

http://www.gndzero.com



Ground Zero Electrostatics TRANSITIONS AND REDUCERS

Conditions or Affects Not Warranted:

- ✱ Exact color or pattern matches
- ✱ Color degradation caused by sunlight or other excessive U.V. rays
- ✱ Any indentation caused by high heels or any other force exceeding 600 p.s.i.
- ✱ Problems caused by excessive moisture, hydro-static pressure, or alkali
- ✱ Abuse or abnormal conditions
- ✱ Exterior applications

WARRANTY TERMS:

Any defects must be reported to Ground Zero within 30 days after the discovery or defect. Always dry lay base before installation to inspect for defects. Ground Zero will not be liable for labor to remove and reinstall defective products that could have been replaced before installation. Ground Zero reserves the right to inspect all claims against our warranties. Ground Zero will not be liable for shipping costs of assumed defective products if the product is found not to be defective.

Ground Zero does not warranty any implied promise or guarantee by any salesmen or representative. Any special condition warranties must be in writing from Ground Zeros president or director of all flooring sales.

TECHNICAL SERVICES

Complete technical services, catalogs and samples are available from the manufacturer and Ground Zero representatives. For information or assistance, contact your Ground Zero representative or a local Ground Zero distributor.

TECHNICAL DATA

Composition

Made of 100% first quality homopolymer vinyl

Installation

Install with high quality solvent-based contact adhesive for compatibility and warranty compliance

Application

All mouldings manufactured for heavy traffic areas

Applicable Standards

Class 1 Fire Rated (ASTM E-648)
New York State Fire Prevention Code
New York City Fire Prevention Code
ADA, OSHA



4916 26th Street West, Suite 100, Bradenton, Florida 34207

Toll Free 877-GND-ZERO (463-1376), **Direct Phone** 941-751-7581 **Fax** 1-941-751-7586

Email sales@gndzero.com

http://www.gndzero.com