



Ground Zero Electrostatics WALL BASE

WALL BASE



Available in a dazzling variety of colors, Ground Zero's wall base is the perfect accessory for our ESD carpets and

tile installations. For any flooring installation, this durable vinyl wall base is the perfect touch for your sensitive electronic production areas.

BENEFITS

- ☀ Available in vinyl & rubber
- ☀ Styles: Cove & Straight Toe
- ☀ Gauge: 0.125", 0.080" (Vinyl Only)
- ☀ Heights: 2-1/2", 4", 6"
- ☀ Lengths: 4' lengths, 120' roll, 160' roll (0.080")
- ☀ Custom color match available: 15 carton/roll minimum (WS-29, WS-40, WS-69, WS-70, WS-79, WS-80)

SPECIFICATIONS

REFERENCES

A. ASTM F 1861-98: Wall Base

WARRANTY

- A. Provide manufacturer's warranty under provisions of Section [01700.] [01740.]
- B. Warranty: Include one year warranty that products are free from defects in materials and workmanship.

PRODUCTS

FLOOR COVERING MATERIALS

A. Base: [ASTM F 1861-98] VPI Wall Base; top set coved, [21/2] [4] [6] inches high, [1/8] [0.080] inch thick, color [selected.] [scheduled.] (Rubber available in 1/8 inch gauge only.)

Pricing for wall base is determined by color. Specify color.

MANUFACTURING TOLERANCES

A. Precision control gauge to assure smooth surface with no high edges.

ADHESIVES

A. Wall Base adhesive: Acrylic Copolymer Wall Base Adhesive or equivalent.

0 calculated VOCs.

EXECUTION

EXAMINATION

- A. Ensure contact wall surface to 1/2 inch below top of base is clean and free from dirt, paint, oil, grease, wall covering, old adhesives, and other extraneous substances.
- B. Beginning of installation means acceptance of surfaces and conditions.

INSTALLATION

- A. Fit top set base joints tight and vertical. Install base on solid backing; adhere tightly to wall surfaces. Miter and form internal and external corners as detailed in manufacturer's installation and maintenance instructions.
- B. Scribe and fit to door frames and other obstructions.

PROTECTION

A. Prohibit traffic on finished floor for 48 hours after installation.

CLEANING

- A. Remove excess adhesive from floor, base, and wall surfaces without damage, while adhesive is still wet.
- B. Clean floor and base surfaces.



4916 26th Street West, Suite 100, Bradenton, Florida 34207

Toll Free 877-GND-ZERO (463-1376), Direct Phone 941-751-7581 Fax 1-941-751-7586

Email sales@gndzero.com

<http://www.gndzero.com>



Ground Zero Electrostatics WALL BASE

PROPERTY	VINYL	RUBBER
TEST DATA		
ASTM 1861-98	Conforms	Conforms
Flame Propagation (UL 992)	<2.0	<2.0
Smoke Density Test (ASTM E 662)	< 450	< 450
Critical Radiant Flux (ASTM E 648 or NFPA 253)	Class I (>0.45 W/cm2)	Class I (>0.45 W/cm2)
CONSTRUCTION		
Composition	High grade resin, thermoplastic binders, fillers, and pigments	High grade resin, thermoplastic binders, fillers, and pigments
Gauge	1/8" **	1/8" **
Lengths	4' lengths or 120' roll	4' lengths or 160' roll
Height	2 1/2", 4", 6" **	2 1/2", 4", 6" **
Style	Cove or Straight Toe	Cove or Straight Toe
INSTALLATION		

WALL BASE PERFORMANCE PROPERTIES

Adhesive & Spread Rate	#600 Wall Base Adhesive; Covers approximately 275 linear feet of 4" base per gallon	#600 Wall Base Adhesive; Covers approximately 275 linear feet of 4" base per gallon
Trowel Size	3/32" x 3/32" triangular notch with 3/32" flats. If applying adhesive with cartridge gun, use a 2-hole nozzle for a 2 1/2", 3-hole nozzle for a 4", and a 5-hole nozzle for 6".	3/32" x 3/32" triangular notch with 3/32" flats. If applying adhesive with cartridge gun, use a 2-hole nozzle for a 2 1/2", 3-hole nozzle for a 4", and a 5-hole nozzle for 6".
WARRANTY		
One Year*		





Ground Zero Electrostatics WALL BASE

COLORS



WB-01
Jet Black




WB-09
Aurora



WB-14
Taupe



WB-16
Cypress




WB-21
Inkwell



WB-23
Sahara



WB-26
Fieldstone



WB-30
Mint



WB-32
Milk Weed



WB-33
Alloy



WB-35
Graphite



WB-36
Silver Sable



WB-42
Cordite



WB-43
Spice



WB-46
Dove



WB-50
Toast



WB-54
Burnt Umber



WB-56
Patriot



WB-59
Plum Wine



WB-60
Tail



WB-63
Smoke



WB-64
Chocolate



WB-66
Charcoal



WB-67
Polaris



WB-74
Papyrus



WB-83
Raisin



WB-86
Tudor



WB-89
Ivy



WB-90
Cappuccino



WB-93
Rainforest



WB-94
Black Brown



WB-97
Fawn




WB-98
London Grey

Custom Colors



WB-29
Arctic



WB-40
Sandstone



WB-69
Pickle



WB-70
Camelback



WB-79
Mustard Seed



WB-80
Terracotta



4916 26th Street West, Suite 100, Bradenton, Florida 34207

Toll Free 877-GND-ZERO (463-1376), Direct Phone 941-751-7581 Fax 1-941-751-7586

Email sales@gndzero.com

<http://www.gndzero.com>