

# CONDUCTIVE/ STATIC DISSIPATIVE ANTI-FATIGUE



## CONDUCTIVE DIAMOND PLATE ANTI-FATIGUE

- Disperse static electricity from an operator the moment they step on the mat and safely away from sensitive equipment.
- 5/32" thick electrically conductive diamond plate surface with a resilient sponge base.
- 9/16" overall thickness with beveled edges.
- Resistivity: Less than 10s OHMS, test method ESD-S7.1 1994.
- Conductive matting should always be used with a ground cord, and the surface kept clean.

CONDUCTIVE DIAMOND PLATE ANTI-FATIGUE		
STOCK NO.	SIZES	WEIGHT EA.
FM-AFC-24X36-1 or 2	24" X 36"	9.0 lbs.
FM-AFC-36X60-1 or 2	36" x 60"	25.0 lbs.
<b>Custom Sizes</b> - available in lengths up to 75 lin. ft.		
STOCK NO.	SIZES	WEIGHT/LIN.FT.
FM.AFD-36-BK-1 or 2*	36"	5.0 lbs.
FM.AFD-48-BK-1 or 2*	48"	6.7 lbs.
<b>Color:</b> Black. *Thicknesses: 1" 9/16", 2 - 1"		



## CONDUCTIVE SMOOTH TOP ANTI-FATIGUE

- Prevent the accumulation of static electricity by quickly draining it from operators and eliminate the hazards of data loss or the damaging of micro-circuitry equipment.
- 1/8" thick conductive smooth surface with a resilient sponge base.
- 1/2" overall thickness with beveled edges.
- Resistivity: Less than 106 OHMS, test method ESD-S7.1 1994.
- Conductive matting should always be used with a ground cord, and the surface kept clean.

CONDUCTIVE SMOOTH TOP ANTI-FATIGUE		
STOCK NO.	SIZES	WEIGHT EA.
FM-AFS-24X36-1 or 2	24" X 36"	9.0 lbs.
FM-AFS-36X60-1 or 2	36" x 60"	23.0 lbs.
<b>Custom Sizes</b> - available in lengths up to 75 lin. ft.		
STOCK NO.	SIZES	WEIGHT/LIN.FT.
FM.AFS-36-BK-1 or 2*	36"	4.5 lbs.
FM.AFS-48-BK-1 or 2*	48"	6.0 lbs.
<b>Color:</b> Black. *Thicknesses: 1 - 1/2", 2 - 7/8		



## STATIC DISSIPATIVE CORRUGATED ANTI-FATIGUE

- Drain harmful static electricity from personnel, safeguard sensitive electronic equipment.
- 1/8" thick static dissipative corrugated surface with a resilient sponge base.
- 1/2" overall thickness with beveled edges.
- Resistivity: Less than 10<sup>6</sup> OHMS, test method ESD-S7.1 1994.
- Static dissipative matting should always be used with a ground cord.

CONDUCTIVE SMOOTH TOP ANTI-FATIGUE		
STOCK NO.	SIZES	WEIGHT EA.
FM-AFC-24X36-1 or 2	24" X 36"	9.0 lbs.
FM-AFC-36X60-1 or 2	36" x 60"	23.0 lbs.
<b>Custom Sizes</b> - available in lengths up to 75 lin. ft.		
STOCK NO.	SIZES	WEIGHT/LIN.FT.
FM.AFC-36-BK-1 or 2*	36"	4.5 lbs.
<b>Color:</b> Black. *Thicknesses: 1 - 1/2", 2 - 7/8		