

ZeroStat Lock Down

Adhesion Enhancer for ZeroStat Crete

Provides
positive
adhesion for
ZeroStat
Crete

Urethane
Modified

Formulated
with new
technology
polymers

PRODUCT DESCRIPTION

Lock Down is a hard surface sealer and adhesion enhancer. When used on very smooth or already coated concrete and other hard surfaces, Lock Down increases the adhesion characteristics of ZeroStat Crete. Lock Down is effective in eliminating curling and chemical attacks of latex and other water-based paints by the water-based solvents used to solubilize the epoxy resin in ZeroStat Crete. Lock Down also aids in adhesion and rapid build of ZeroStat Crete when recoating or repairing worn areas.

APPLICATION & MAINTENANCE

Thoroughly scrub floor with a good degreaser or ZeroStat Citrus to remove all dirt, grease, or oil. Remove stripping solution with a wet vacuum, auto-scrubber, or mop. Rinse the floor completely with clean water and allow it to dry. Apply Lock Down in thin even coats with a clean mop or applicator. Depending on the condition of the floor, one or two coats generally provide satisfactory results. To insure complete curing, allow approximately two hours between the last coat of sealer and the first coat of ZeroStat Crete.

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Product No.

20B

This material is not a hazardous mixture as defined in 29 CFR 1919, 1200 and M.G.L. c. 111F. Safety glasses and gloves should be worn during application and handling. If ingested, drink milk, water, or fruit juice and induce vomiting with oil of ipecac. In the event of eye contact, flush area with water for 15 minutes. **Consult with a physician.** For detailed information, consult MSDS sheet.

SPECIFICATIONS

Nonvolatile Solids	22 ± 0.6%
Total Active	28%
pH	8.2 - 90
Color	Translucent white
Weight Per Gallon	8.42
Slip Resistance (ASTM)	0.55 minimum
Stability	2 years minimum at room temperature
Freeze/Thaw Stability	3 cycles minimum
Drying Time	30 - 45 minutes
Adhesion	Very Good
Water Resistance	Excellent
Gallon Coverage (Feet ²)	2000 ± 10%
Removability (Gardner)	75 cycles maximum

**GROUND
ZERO
ELECTROSTATICS**

P.O. BOX 70
Bradenton, Florida 34206
Toll Free: 877-463-1376
Direct Phone: 941-751-7581