



# Ground Zero Electrostatics ULTRAEARTH RUBBER FLOORING

## UltraEarth Rubber Flooring



Drawn from the richness of clays, woods and sand, UltraEarth offers 14 warm, vibrant tones inspired by Mother Nature herself.

The green in Moss appeal is reminiscent of lush fields. The reds in Brickhouse imitate the richness of Georgia clay. And only coal miners have seen charcoals deeper than Coal Porter.

UltraEarth flooring offers durability and resilience that can't be beat. Made from high-quality, reprocessed EPDM rubber, it feels great underfoot and offers slip-resistance that grabs you. UltraEarth is right in line with the new ASTM Sustainability Assessment (ASTM E2129-01). This new practice celebrates the green properties and sustainability of ECO surfaces products, raw materials and manufacturing processes. Waste not - want not. This is all about protecting our natural resources. Plus, all UltraEarth surfacing is available in roll and tile forms. Offering such rich color, UltraEarth is out-of-this-world!

### FEATURES AND BENEFITS

- ☐ Complies with new ASTM Sustainability Assessment
- ☐ Single-ply, non-laminated
- ☐ Indoor and outdoor
- ☐ Outstanding slip-resistance
- ☐ Unbelievable durability
- ☐ Cushioned resilience
- ☐ Stain resistance
- ☐ Consistent color (no wear layer)
- ☐ Low VOC emissions
- ☐ Custom colors
- ☐ Logo/graphic inlays
- ☐ Easy installation/maintenance

### ITEM NUMBERS

Color	Item Number
Coffee & Cream	FM-UE-48-701
Coal Porter	FM-UE-48-703A
Brickhouse	FM-UE-48-704
Mountain Majesty	FM-UE-48-708
Pumpkin Patch	FM-UE-48-709
Rare Earth	FM-UE-48-710
Blue Danube	FM-UE-48-713
Blue Bayou	FM-UE-48-714
Blueberry Hill	FM-UE-48-715
Hot Tamale	FM-UE-48-716
Cinnamon Toast	FM-UE-48-717
Bit O' Honey	FM-UE-48-718
Cate Moss	FM-UE-48-719
Appletini	FM-UE-48-720
Iced Frappuccino	FM-UE-48-721

### VARIOUS DIMENSIONS:

ROLLS	
Width:	48"
Thickness:	4mm (5/32") standard 6mm (1/4") special - Min. 1600 sq. ft. increments ONLY
Weight:	4mm 1.1lbs/sq.ft. 6mm 1.7lbs/sq.ft.
Length:	200 sq/ft (50 l/ft) per roll
TILE	
Size:	36" x 36" 18" x 18"
Thickness:	4mm (5/32") standard 6mm (1/4") special - Min. 1600 sq. ft. increments ONLY





# Ground Zero Electrostatics ULTRAEARTH RUBBER FLOORING

## SPECIFICATIONS

Test	ASTM	EPDM
Tensile Strength	D412	200 lb/in <sup>2</sup> min
Flexibility	F137	Pass ¼ inch mandrel
Coefficient of Friction	D2047	>0.9
McBurney Indentation	F142, 1 min	0.0080 inches
Thermal Conductivity	C518	0.445 Btu-in/hr-ft <sup>2</sup> -°F
Static Load Limit	F970, 400 lbs	<0.005 in
Chemical Resistance	F925	slight change
Impact Insulation	Class E492	48
Sound Transmission Coefficient	E413	51
Noise Reduction Coefficient	C423	0.05 sabine/ft <sup>2</sup>
Sustainability	E2129-01	data collected

## COLORS

	Coffee & Cream FM-UE-48-701		Coal Porter FM-UE-48-703A
	Brickhouse FM-UE-48-704		Mountain Majesty FM-UE-48-708
	Pumpkin Patch FM-UE-48-709		Rare Earth FM-UE-48-710
	Blue Danube FM-UE-48-713		Blue Bayou FM-UE-48-714
	Blueberry Hill FM-UE-48-715		Hot Tamale FM-UE-48-716
	Cinnamon Toast FM-UE-48-717		Bit O' Honey FM-UE-48-718
	Cate Moss FM-UE-48-719		Appletini FM-UE-48-720
	Iced Frappuccino FM-UE-48-721		

## INSTALLATION

Basic installation procedures and tools are the same as for other standard commercial resilient flooring and should be installed by experienced floor-covering mechanics. Instructions are outlined in the UltraEarth technical manual must be followed.

## MAINTENANCE

GZ Rubber Flooring must be maintained as recommended. The type and frequency of maintenance will vary according to maintenance equipment and desired appearance of product.

